

Industrie PC „VIS-ACP-2020MB-i306“

Kompletter 2HE Industrie Rackmount PC inkl. Mainboard, RAM und Intel Core i3 Prozessor

Artikel-Nummer:

VIS-ACP-2020MB-i306



Weitere Konfigurationen auf Anfrage!

Industrie
Computer **1**

Panel
Computer **2**

Industrie
Displays **3**

Medical
Computer **4**

Automation **5**

Software **6**

- 2 HE Industrie PC Gehäuse
- Intel Core i3 Prozessor

- Industrie Mainboard
- Komplett montiert und getestet

Industrie Rackmount PC / 2HE
Front USB, Alarmboard mit Front LEDs

- Gehäuse: ACP-2020MB (350W 80+ Indus.-PS)
- Industrie-Mainboard: AIMB-788G2 (DP/HDMI/VGA, 2x GB-LAN, 8x USB ...)
- CPU: INTEL Core i3-14100 3.5GHz (max. 4.7GHz) inkl. Kühler
- Speicher: 16GB DDR4-3200 (2x 8GB)
- Festplatte: 256GB SSD M.2 2280 TLC Industrial Grade
- Laufwerke: -
- Sonstiges: -
- Gerät montiert inkl. SI Prüfbericht und 24h Systemtest
- Garantie: 2 Jahre (bring in)

ACP-2020

2U Rackmount Short Depth Chassis for ATX and uATX Motherboard



Features

- 398 mm short depth 2U rackmount chassis
- Supports ATX and uATX form factor single processor motherboard
- Two Internal 2.5" drive bay and two "hot-swap or external" drive bay
- Supports 80 Plus single 350W/500W or 500W redundant power supply
- Front-accessible system fan without opening top cover for easy maintenance
- Built-in Intelligent System Module enabling whole system fan control and remote manageability

CE FCC


Specifications

Drive Bay	Slim Optical Drive	External	Internal
		1	-
	2.5"	2 (hot-swap tray module as optional)*	2
Cooling	Fan	1 (8 cm/46.62CFM)	
	Air Filter	Yes	
Front I/O Interface	USB 3.0*	2	
Miscellaneous	LED Indicators	Power, HDD, temperature, fan, LAN1, and LAN2	
	Rear Panel	Two 9-pin D-Sub	
Intelligent System Module Hardware Monitoring	CPU/System fan speed, CPU/System temperature (Only Advantech AIMB-78X, PCE-51XX/71XX mainboards can enable CPU fan speed and temperature monitoring function of Intelligent System Module)		
Environment	Temperature	Operating	Non-Operating
		0 ~ 40 °C (32 ~ 104 °F)	-20 ~ 60 °C (-4 ~ 140 °F)
	Humidity	10 ~ 85% @ 40 °C, non-condensing	10 ~ 95% @ 60 °C, non-condensing
	Vibration (5 ~ 500 Hz)	1 Grms	2 G
	Shock	10 G (with 11 ms duration, half sine wave)	
Physical Characteristics	Dimensions (W x H x D)	482 x 88 x 398 mm (19" x 3.46" x 15.7")	
	Weight	8.6 kg (18.96 lbs)	


The USB 3.0 ports do not operate if the motherboard has no on-board USB 3.0 box header.

* ACP-2020 2.5" drive bay, both default internal and hot-swap tray module support 2.5" HDD with thickness less than 14.7mm.


Front View



Rear View




Top View



Dimensions

Unit: mm [inch]



Ordering Information

Part Number	Power supply	80 Plus grade	Power supply type	Wattage	Switch
ACP-2020MB-35B	PS8-350FATX-GB	Gold	Single Flex ATX	350W	ATX
ACP-2020MB-50RE	RPS8-500U2-XE	Bronze	1+1 redundant	500W	ATX
ACP-2020MB-50B	PS8-500FATX-GB	Gold	Single Flex ATX	500W	ATX

Packing List

Part Number	Description	Quantity
ACP-2020	2U rackmount chassis with handle set	1
1750009329-01	system fan	1
1700024778-11	system fan cable	1
Content of Accessory Box		
98R22020000	Handle set	1
	Screws/nuts and rubber for motherboard and devices	one bag
1960073134N000	HDD convert bracket, 3.5" to dual 2.5" (max T:14.7mm)	2
2001202000	user manual	1

Optional Accessories

Part Number	Description
96CB-SATAPOWER-6P2	SATA power wire 6-pin to big 4-pin (for slim ODD)
1990021407T000	Door filter
98R1310010E	2.5" SATA/SAS Hot-swap module
ASMB-RM2F4-11A1	2U riser card with 1 PCIe16 & 1 PCIe4 expansion
Rear I/O panel kit for low-profile add-on cards	
1939000361	Screws (should purchase 7 pcs)
1960074850T000	I/O bracket (should purchase 7 pcs)
1960019475T206	Rear panel for low-profile